



# Functions Guide

## Table of Contents

<b>I. Introduction</b>	<b>3</b>
<b>II. Function Descriptions</b>	<b>4</b>
A. Session Functions	4
1) PCQB_BeginSession( CompanyFile ; ShareMode ; optHideFMWindow )	4
2) PCQB_EndSession	5
3) PCQB_Browse	5
4) PCQB_GetCurrentFileName	5
5) PCQB_GetCurrentFileVersion	5
B. Request Functions	6
1) PCQB_RqNew( MessageType ; optAttributes )	6
2) PCQB_RqAddFieldWithValue( QBFieldName ; Value ; optAttributes )	6
3) PCQB_RqAddRelatedRecord( Type ; optValue ; optAttributes )	7
4) PCQB_RqCloseRelatedRecord	7
5) PCQB_RqExecute ( optHideFMWindow ; optFilter ; optPath )	8
6) PCQB_RqUseXML( XMLText ; optIsPath)	8
C. Response Functions	9
1) PCQB_RsOpenFirstRecord	9
2) PCQB_RsOpenNextRecord	9
3) PCQB_RsGetFirstFieldValue( QBFieldName )	9
4) PCQB_RsGetAttribute( AttributeName )	10
5) PCQB_RsGetResponseAttribute( AttributeName )	10
6) PCQB_RsOpenFirstRelatedRecord( Type )	10
7) PCQB_RsOpenNextRelatedRecord	11
8) PCQB_RsCloseRelatedRecord	11
9) PCQB_RsUseXML( XML ; optIsPath ; optFilter )	11
D. Other Functions	12
1) PCQB_SGetXML( Type ; optPath )	12
2) PCQB_SGetStatus	12
3) PCQB_SFormatString( String ; qbType )	12
E. Registration Functions	13
1) PCQB_GetOperatingMode	13
2) PCQB_Register( ServerName ; ServerPort ; ServerPage ; LicenseID )	13
3) PCQB_Version( Type )	13
F. Z Functions (FileBooks Link Migration Functions)	14
1) PCQB_ZCloseConnection	14
2) PCQB_ZDeleteFile( FilePath )	14
3) PCQB_ZExecute( XPath ; qbXML ; optFilePath )	14
4) PCQB_ZModify( XPath ; Object ; SearchCriteria ; Modifications ; optFilePath )	15
5) PCQB_ZParseXML( XML ; IsPath ; Xpath ; optFilePath )	15
6) PCQB_ZQuery( XPath ; Object ; optSearchCriteria ; optFilePath )	16
7) PCQB_ZResetQBOE	16
8) PCQB_ZValidateXML( XML ; IsPath )	16
<b>III. Contact Us</b>	<b>17</b>

## I. Introduction

### **Description:**

The FM Books Connector plug-in is a powerful tool used to move data between FileMaker® Pro and Intuit QuickBooks® applications. In this Functions Guide we will describe all available FileMaker functions, parameters, return values and error handling.

### **Intended Audience:**

FileMaker developers or persons, who have knowledge of FileMaker scripting, calculations and relationships as proper use of the plug-in requires that FileMaker integration scripts be created in your FileMaker solution.

### **Successful Integration Practices:**

- 1) Read the Developer's Guide
- 2) Familiarize yourself with basic accounting practices and QuickBooks
- 3) Read the Functions Guide
- 4) Use the OSR (Intuit's Onscreen Reference Manual)

OSR can be found here: <http://developer.intuit.com/qbsdk-current/Common/newOSR/index.html>

- 5) Look at our FileMaker Demo and video tutorials

Demo and video tutorials can be found here: <http://www.fmbooksconnector.com>

- 6) Re-read the Developer's Guide

### **Error Handling:**

Any of the plug-in functions may encounter an error during processing. The function will return the string "**!!! ERROR!!**". When an error occurs during processing, immediately call the PCQB\_SGetStatus function in order to obtain a full description of the error. This function returns the message associated with the last error. The status is used to identify errors in the request or the processing of requests. The text returned by this function will help troubleshoot script or logic failures.

## II. Function Descriptions

This section of the document describes the available FileMaker plug-in functions.

### A. Session Functions

#### 1) PCQB\_BeginSession( CompanyFile ; ShareMode ; optHideFMWindow )

##### **Description:**

This function begins a session working with the specified QuickBooks company file in the specified mode.

##### **Parameters:**

CompanyFile = A full path to the desired QuickBooks company file.

If QuickBooks is already launched with an open company file, this value can be an empty string and FM Books Connector will attach to the currently open company file. If no file is open and no company file is specified, an error occurs. If a company file is opened and is different than that specified an error occurs. (If this call succeeds with an empty string for this parameter, or an error is returned, you can obtain the name of the currently open company file by calling the PCQB\_GetCurrentFileName function.)

Share Mode = Identifies if QuickBooks will be available to other users while the plug-in has it opened. Following are acceptable values:

"Single"; FM Books Connector has exclusive access to QuickBooks for this file, or shares with the current user.

"Multi"; allows FM Books Connector to share access to the specified company file with other applications as well as with a user who is interacting directly with the company file through QuickBooks.

Please see Table 1 below for a listing of the effects of the mode on file access.

optHideFMWindow = Optional - If this parameter = "Y" then the FileMaker Pro window is hidden from the user until the function returns. A dialog is displayed in its place. This should be used when execution takes longer than 2 seconds.

##### **Return Values:**

0 for success, or an error

**Table 1 : Effects of mode on QuickBooks operation**

Who started QuickBooks	Selected Mode	Who else may obtain access
FM Books Connector	"Single"	No one else
FM Books Connector	"Multi"	QuickBooks user on same machine = no access All other integrated applications = access QuickBooks users on other machines = access
QuickBooks User	"Single"	QuickBooks user already logged in Only one integrated application = access
QuickBooks User	"Multi"	QuickBooks users = access Integrated applications = access

## **2) PCQB\_EndSession**

### **Description:**

This function ends the current session with the QuickBooks file. After the session is ended file access is returned to the default for the file.

**Parameters:** none

### **Return Values:**

0 for success or an error.

## **3) PCQB\_Browse**

### **Description:**

This function displays file browser dialog for locating a QuickBooks company file. The full path to the select file is returned on 'OK'

**Parameters:** none

### **Return Values:**

A full path to the selected file is returned.

## **4) PCQB\_GetCurrentFileName**

### **Description:**

This function returns the name of the file that is currently attached to the session. There must be a session established in order to return the file name.

**Parameters:** none

### **Return Values:**

The name of the QuickBooks company file is returned.

## **5) PCQB\_GetCurrentFileVersion**

### **Description:**

Use this function to determine which SDK version is supported by the currently opened file. This function is generally used for development and troubleshooting purposes.

**Parameters:** none

### **Return Values:**

The SDK Version in string format or an error is returned

## B. Request Functions

### 1) PCQB\_RqNew( MessageType ; optAttributes )

#### **Description:**

This function creates a new Request of the desired type.

#### **Parameters:**

MessageType = See the 'OSR' for valid Message Types and meanings.

opt Attributes = Allows the user to set the attributes of particular nodes in underlying qbXML.  
Available Attributes for any node are listed in the OSR next to the node in parenthesis.

#### **Return Values:**

0 for success otherwise an error is returned.

### 2) PCQB\_RqAddFieldWithValue( QBFieldName ; Value ; optAttributes )

#### **Description:**

This function is used to add a field and value to the current request. The function will automatically format the Value parameter for use with QuickBooks if the field identified by the QBFieldName function is of one of the following types:

BOOLTYPE, DATETYPE, DATETIMETYPE, QUANTTYPE, PERCENTTYPE, PRICETYP, AMTTYPE, INTTYPE  
Other types are formatted as entered.

#### **Parameters:**

QBFieldName = The name of the QuickBooks field to be added to the request.  
See the 'OSR' for valid field names.

Value = The value to be inserted for the specified field.

opt Attributes = Allows the user to set the attributes of particular nodes in underlying qbXML.  
Available Attributes for any node are listed in the OSR next to the node in parenthesis.

Example for an Invoice: PCQB\_RqAddFieldWithValue ("RefNumber" ; TheirInvoicenumber )

#### **Return Values**

0 for success otherwise an error.

### **3) PCQB\_RqAddRelatedRecord( Type ; optValue ; optAttributes )**

#### **Description:**

This function adds related records to the request. The related record becomes active until the PCQB\_RqCloseRelatedRecord function is called. Calls to PCQB\_RqAddFieldWithValue and PCQB\_RqAddRelatedRecord will add fields and records to the currently active record until PCQB\_RqCloseRelatedRecord is called.

**\*\*The RqAddRelatedRecord now behaves identical to the RqAddFieldWithValue with the exception that it will create new nodes and apply the optValue to the new node instead of overwriting any current nodes. This is very useful when dealing with 1-n nodes that contain values. See the FullName node in the GeneralDetailReportQuery object in the OSR\*\***

#### **Parameters:**

Type =	The type of related record to be added.
optValue =	The value to be inserted for the specified field.
opt Attributes =	Allows the user to set the attributes of particular nodes in underlying qbXML. Available Attributes for any node are listed in the OSR next to the node in parenthesis.

#### **Returns:**

0 for success otherwise and error

### **4) PCQB\_RqCloseRelatedRecord**

#### **Description:**

This function closes the related record and sets the active record to its parent.

#### **Parameters: none**

#### **Returns:**

0 for success otherwise an error.

## **5) PCQB\_RqExecute ( optHideFMWindow ; optFilter ; optPath )**

### **Description:**

This function posts the request to QuickBooks. If the request is processed by QuickBooks a set of records will be created in a response and held in memory for parsing. If the request is not valid or some other error has occurred then an error is returned.

### **Parameters:**

optHideFMWindow = Optional - If this parameter = "Y" then the FileMaker Pro window is hidden from the user until the function returns. A dialog is displayed in its place. This should be used when execution takes longer than 2 seconds.

optFilter = Optional XPath string that will filters the response from QuickBooks. If left empty or omitted the response is not filtered

optPath = Optional absolute path where the response will be saved as a file. If empty or omitted the response is not saved to a file.

### **Returns:**

0 for success otherwise an error.

## **6) PCQB\_RqUseXML( XMLText ; optIsPath)**

### **Description:**

The FM Books Connector uses XML to communicate with QuickBooks. The several functions offered by the plug-in are used to create the qbXML requests. In some scenarios the end user might want to use pre-defined qbXML requests. This function allows the user to pass a pre-defined qbXML request to the plug-in.

### **Parameters:**

XMLText = The entire XML text that will be used as the request or a path to an xml file

optIsPath = Optional Boolean value indicating if XMLText is a path to a file or if XMLText contains actual XML data. Default value is false

### **Returns:**

0 for success otherwise an error.



## C. Response Functions

### 1) PCQB RsOpenFirstRecord

**Description:**

Since a response may include several records it is necessary to be able to iterate through these records. This function will access the first record in the response. Use PCQB\_RsOpenNextRecord to iterate through the rest of the records in the response.

**Parameters: none****Return Values:**

0 for success, 'End' if there are no records in the response, or an error.

### 2) PCQB RsOpenNextRecord

**Description:**

This function opens the sibling record of the current record, or the next record in the response. The record becomes the active record for reading.

**Parameters: none****Returns:**

0 for success, 'End' if there are no more records in the response, or an error.

### 3) PCQB RsGetFirstFieldValue( QBFieldName )

**Description:**

Returns the value stored in the first field with the name specified by Name

**Parameters:**

QBFieldName =       The name of the field from which to retrieve the value.  
                          See the 'OSR' for valid field names.

**Returns:**

The value stored in the field or an error.

#### **4) PCQB RsGetAttribute( AttributeName )**

**Description:**

**\*\*Still under development\*\***

Allow the user to parse reposts generated by QuickBooks.

**Parameters:**

AttributeName = **\*\*Still under development\*\***

**Returns:**

**\*Still under development\*\***

#### **5) PCQB RsGetResponseAttribute( AttributeName )**

**Description:**

**\*\*Still under development\*\***

Allow the user to parse reposts generated by QuickBooks.

**Parameters:**

AttributeName = **\*\*Still under development\*\***

**Returns:**

**\*Still under development\*\***

#### **6) PCQB RsOpenFirstRelatedRecord( Type )**

**Description:**

This function sets the active record to the first record of the specified type.

**Parameters:**

Type =                      The type of related record to open.  
See the 'OSR' for valid Types aka Element Names.

**Returns:**

0 for success or an error.

## **7) PCQB\_RsOpenNextRelatedRecord**

### **Description:**

This function opens the sibling record of the current record, or the next related record. The record becomes the active record for reading.

### **Parameters: none**

### **Returns:**

0 for success, 'End' if there are no more records in the response, or an error.

## **8) PCQB\_RsCloseRelatedRecord**

### **Description:**

This function closes the related records and returns to the parent record. The parent becomes the active record and is available for parsing using the several Response functions.

### **Parameters: none**

### **Returns:**

0 on success or an error.

## **9) PCQB\_RsUseXML( XML ; optIsPath ; optFilter )**

### **Description:**

The FM Books Connector uses XML to communicate with QuickBooks. Several functions offered by the plug-in are used to create the qbXML requests. In some scenarios the user might want to use pre-defined qbXML requests. This function allows the user to pass a pre-defined qbXML response to the plug-in.

For example: This function is used to load a valid response from QuickBooks into the parser. Once the response is loaded in the parser, it is available to the other PCQB\_RsXXXX functions.

### **Parameters:**

XML =	The entire XML text that will be used as the request or path to xml file.
optIsPath =	Optional Boolean value indicating if XML Text is a path to a file or if XML Text contains actual XML data. Default value is false.
optFilter =	Optional XPath string that will filter the response from QuickBooks. If left empty or omitted the response is not filtered.

### **Returns:**

0 on success or an error.

## D. Other Functions

These functions are mostly for debugging purposes

### 1) PCQB\_SGetXML( Type ; optPath )

**Description:**

This function returns the request or response XML text in its entirety.

**Parameters:**

Type =	Either "Request" to get the current text or "Response" to get the response text
optPath =	Optional absolute path where the xml will be saved as a file. If omitted then the xml is not saved to a file

**Returns:**

The XML text or an error.

### 2) PCQB\_SGetStatus

**Description:**

This function is used to retrieve a verbose explanation of errors. Immediately after an error is returned please call PCQB\_SGetStatus to obtain a full description of the error. This function returns the message associated with the last error. The status is used to identify errors in the request or the processing of requests. The text returned by this function helps the user to troubleshoot script or logic failures.

**Parameters: none****Returns:**

This function returns a description of the last error to occur.

### 3) PCQB\_SFormatString( String ; qbType )

**Description:**

This function returns the String parameter properly formatted for use with the desired qbType.

This function is used to format a string for use with a specific QuickBooks field type. The function returns the exact same value that will be used with the PCQB\_RqAddFieldWithValue function

**Parameters:**

String =	The value to be formatted. "Response" to get the response text
qbType =	The qbXML /QuickBooks type for which the string will be formatted. Acceptable values are: BOOLTYPE, DATETYPE, DATETIMETYPE, QUANTTYPE, PERCENTTYPE, PRICETYPE, AMTTYPE, INTTYPE, TIMEINTERVALTYPE, STRTYPE

**Returns:**

The string properly formatted for the desired qbType or an error.

## E. Registration Functions

The plug-in offers the following functions for registration and plug-in checker purposes.

### 1) PCQB\_GetOperatingMode

**Description:**

This function returns the operating mode of the plug-in.

**Parameters: none**

**Returns:**

'DEMO' for demo mode indicating that all plug-in functions accessible with demo limitations.

'LIVE' for live mode indicating that all plug-in functions accessible without limitation.

'UNREGISTERED' for unregistered mode indicating that the plug-in functions are not accessible.

### 2) PCQB\_Register( ServerName ; ServerPort ; ServerPage ; LicenseID )

**Description:**

The plug-in must be registered with Productive Computing, Inc before use. This function registers the plug-in. The values for each of the parameters of this function are supplied by Productive Computing.

**Parameters:**

ServerName	=	"licensing.productivecomputing.com"
ServerPort	=	"80"
ServerPage	=	"/PCIReg/pcireg.asp"
LicenseID	=	"your license ID or DEMO-FMBC"

**Returns:**

0 for success or an error.

### 3) PCQB\_Version( Type )

**Description:**

This function returns the current version of the plug-in.

**Parameter:**

type = 'Short' or 'Long'

The short version string includes only the version number of the plug-in. For example: "1.0.5.7".

The long includes the plug-in name and version number. For example: "FM Books Connector 1.0.5.7"

The default version string returned is short.

**Returns:**

The version string and/or name of the plug-in.

## **F. Z Functions (FileBooks Link Migration Functions)**

The following 'Z' functions were created for the sole purpose of migrating from FileBooks Link to FM Books Connector. These functions should only be used by Developers who are following the procedures from the accompanying Migration Guide.

### **1) PCQB ZCloseConnection**

**Description:**

Ends any session with QuickBooks and closes the connection to the QuickBooks application

**Parameters:**

None

**Returns:**

0 on success otherwise "!!ERROR!!"

### **2) PCQB ZDeleteFile( FilePath )**

**Description:**

The function deletes a file on the local system

**Parameters:**

FilePath =                      The path to the file to be deleted

**Returns:**

0 on success otherwise "!!ERROR!!"

### **3) PCQB ZExecute( XPath ; qbXML ; optFilePath )**

**Description:**

The function posts the qbXML to QuickBooks as a request.

**Parameters:**

XPath =                      Contains the XPath query to be applied to the desired XML  
qbXML =                      Valid qbXML formatted text  
optFilePath =                Optional parameter indicating a file to save the results of the XPath query. If left empty (or if the final semicolon and parameter are omitted entirely) the results will not be saved.

**Returns:**

On success the result of the XPath query applied to the response or the error string "!!ERROR!!"

#### **4) PCQB ZModify( XPath ; Object ; SearchCriteria ; Modifications ; optFilePath )**

##### **Description:**

The function modifies an existing QuickBooks record based on the parameters passed to the function. A query is performed to locate the record, then the modifications are applied to the found record.

##### **Parameters:**

XPath =	Contains the XPath query to be applied to the desired XML
SearchCriteria =	Contains XML fragments that will be applied to the search. For example, when searching for a customer whose name is "Sample Customer", the text required in the search criteria parameter would simply be, "<FullName>Sample Customer</FullName>".
Object =	Any object in QuickBooks that responds to the query request, such as Host, Company, Customer, Invoice, and many more. See the appendix for available objects.
Modifications =	Contains XML fragments that will be applied to the record found by the Object query. For example, when modifying the phone number the value for the parameter would be "<Phone>somePhoneNumber</Phone>".
optFilePath =	Optional parameter indicating a file to save the results of the XPath query. If left empty the results will not be saved.

##### **Returns:**

The result of the XPath query or the error string "!!ERROR!!"

#### **5) PCQB ZParseXML( XML ; IsPath ; Xpath ; optFilePath )**

##### **Description:**

The function returns the result of an XPath query applied to an XML document.

##### **Parameters:**

XML =	Contains the text of the XML document or a path to an XML document stored on the local hard disk. This is the XML that will be queried with the XPath.
IsPath =	A Boolean operator indicating whether or not the XML argument is a path to a file. A 'True' value indicates the XML argument is a path to a file.
XPath =	Contains the XPath query to be applied to the desired XML
optFilePath =	Optional parameter indicating a file to save the results of the XPath query. If left empty the results will not be saved.

##### **Returns:**

The result of the XPath query or the error string "!!ERROR!!"

## **6) PCQB ZQuery( XPath ; Object ; optSearchCriteria ; optFilePath )**

### **Description:**

The function queries QuickBooks for existing QuickBooks records based on the parameters passed to the function.

### **Parameters:**

XPath =	Contains the XPath query to be applied to the desired XML
optSearchCriteria =	Contains XML fragments that will be applied to the search. For example, when searching for a customer whose name is "Sample Customer", the text required in the search criteria parameter would simply be, "<FullName>Sample Customer</FullName>". This parameter is optional and if omitted all records matching the desired object are queried.
Object =	Any object in QuickBooks that responds to the query request, such as Host, Company, Customer, Invoice, and many more. See the appendix for available objects.
optFilePath =	Optional parameter indicating a file to save the results of the XPath query. If left empty (or if the final semicolon and parameter are omitted entirely) the results will not be saved.

### **Returns:**

On success the result of the XPath query applied to the response or the error string "!!ERROR!!"

## **7) PCQB ZResetQBOE**

**\*\*Coming soon\*\***

## **8) PCQB ZValidateXML( XML ; IsPath )**

### **Description:**

This function validates the desired XML against the qbXML schema for the currently opened QuickBooks file.

### **Parameters:**

XML =	A string containing the desired qbXML or a path to the document containing the desired qbXML
IsPath =	A Boolean operator indicating whether or not the XML argument a path to a file. A 'True' value indicates the XML argument is a path to a file.

### **Returns:**

0 if the desired XML is a valid qbXML document for use with the currently opened file or "!!ERROR!!"



### III. Contact Us

Successful integration of our products within your own system requires a working knowledge of FileMaker, especially in the areas of scripting and calculations. If you need additional support for scripting, customization or setup, then you can contact us via the avenues listed below.

Phone: 760-510-1200

Email: [support@productivecomputing.com](mailto:support@productivecomputing.com)

Forum: [www.productivecomputing.com/forum](http://www.productivecomputing.com/forum)

However please note that assisting you with implementing this plug-in (excluding registration) is billable at our standard rate. We bill on a time and materials basis so you are only billed for the time it takes to assist you. If you are not a FileMaker Developer or are just too busy to create the integration scripts, then please contact us. We will be happy to provide you with a free estimate to create your integration scripts. We are ready to assist and look forward to hearing from you!